ELECTRIC WATER HEATER

3.6kW AND 5kW



PART NUMBERS:

3.6kW Electric Water Heater - 3C-6693-0A00 5kW Electric Water Heater - 3C-6694-0A00

ELECTRIC WATER HEATER FEATURES


Whether you need to create a warm, comfortable and safe environment for passengers and/or drivers, or provide the optimum temperature for your vehicle's batteries, our Electric Water Heater can provide the solution.


Our electric water heater will deliver critical heat to your full electric, hydrogen or hybrid vehicles' drivers, passengers or batteries. Noise-free and completely emission-free, our high-performance heater range are the electric water heaters of choice for market-leading bus, coach, commercial vehicles, refuse trucks, off-highway and stationary power manufacturers.


Key features

- Heat output either 3.6kW or 5kW @ 650VDC input voltage
- Built-in thermal protection for safety
- Ideal for remote installation or packaging as part of a complete system
- Optimises efficiency and life of batteries in cold climates
- Additional heating source in a heat pump when operating in low ambient conditions
- Manufactured with insulated body to minimise energy losses
- Lightweight and compact solution
- "Plug and Play" installation
- Zero maintenance
- Supplied with a standard high voltage electrical connector

DIMENSIONS













CAVITY No	COLOUR
1	RED
2	BLACK

TECHNICAL INFORMATION

Electric Water Heater (3.6kW and 5kW)

Water heating capacity @ 650VDC Working Temperature of the Liquid Installation Temperature Working Pressure	3.6kW & 5kW -30°C to +80°C -30°C to +50°C 2 bar max
Minimum flow rate	15 I/min
Nominal Voltage	650V DC
Operating Voltage Range	300V - 800V DC
Nominal Power	3600W +5/-10% or 5000W +5/-10%
Maximum weight (without coolant) (kg)	3kg
External Dimensions (mm)	494mm (L) x 152mm (D) x 205mm (H)
External Dimensions (mm) Connector types (High Voltage (4-Pin)	494mm (L) x 152mm (D) x 205mm (H) TE Connectivity (PA66-GF35) Deutsch (HDP24/26)
Connector types (High Voltage (4-Pin)	TE Connectivity (PA66-GF35) Deutsch (HDP24/26)
Connector types (High Voltage (4-Pin) Inlet & Outlet Size (mm)	TE Connectivity (PA66-GF35) Deutsch (HDP24/26) 28 mm

